>

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau

AIPO



(43) International Publication Date 8 January 2004 (08.01.2004)

PCT

(10) International Publication Number WO 2004/002677 A1

(51) International Patent Classification7:

B24B 11/10

(21) International Application Number:

PCT/KR2003/001258

(22) International Filing Date:

26 June 2003 (26.06.2003)

(25) Filing Language:

Korean

(26) Publication Language:

English

(30) Priority Data: 10-2002-0035938

26 June 2002 (26.06.2002) KI

(71) Applicant and

(72) Inventor: SIM, Sang-Bae [KR/KR]; 5-102, Yaksoo Apt., 216, Sangdo 5-dong, Dongjak-ku, Seoul 156-035 (KR).

(74) Agent: LIM, Young-Hee; Sinmyong Bldg., 3rd Floor, 645-21, Yoksam-dong, Kangnam-ku, Seoul 135-080 (KR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: BOWLING BALL RESURFACING APPARATUS



(57) Abstract: A bowling ball resurfacing apparatus comprises a housing, first and second vertical support rollers mounted to the housing for rotation about parallel vertical axes, each of the vertical support rollers adapted to make contact with the surface of the bowling ball at one lateral bottom side of the bowling ball, first and second horizontal support rollers mounted to the housing for supporting the bowling ball in cooperation with the vertical support rollers, each of the horizontal support rollers rotatable about horizontal axes and adapted to make contact with the surface of the bowling ball at the other lateral bottom side of the bowling ball, drive motors for causing the support rollers to rotate, and a grinding-and-polishing wheel assembly for making frictional contact with the surface of the bowling ball to grind or polish the bowling ball.